

Ink Storage

S.S. material tray for ink storage.

The upper rollers are manufactured by solid rods with herned Rubber coating for high clarity of printing with minimum consumption of lnk. The Rubber roller is in tandem with the another Rubber roller.



## Alert Light:

Machine working alert by light indication. If machine stops than green light will blink, if emergency stop than red light will blink.



### Bag Feeding STOPPER ATTACHMENT:

Draw rollers actuated by adjustable cam for synchronizing with STOPPER ATTACHMENT to print at exact position of bag there by eliminating judgement of operator.



## Inching System given at Each Drum:

At each drum we provide power switch to rotate drum as per requirement at time of stereo setting. It reduces workers stereo setting time & very easy to set stereo. Also ease at the time of cleaning drum and belt.



Emergancy Stop: At Center Side of machine.

We provide Emergancy Stop switch. It reduces your rejection of bags & you can neglect accident.



# Pannel Board / A.C. Drive:

A.C. frequency converter (A.C. Variable speed drives) of Delta make with separate potentionmeter, ON-OFF switch shall be fitted for the easy operation.



Bag Counter Meter:

For Counting no. of bags Counter meter with sensor.




**Extended Drying** Time:

Ink Drying time extended to dry printing impression on bag.



- Alert Light
- **6)** Bag Feeding STOPPER **ATTACHMENT**
- 4 Pannel Board / A.C. Drive
- 6 Emergancy Stop
- 6 Inching System given at **Each Drum**
- Bag Counter Meter
- 8 Extended Drying Time
- Ink Drying



Ink Drying: ULTRA VIOLET light / HEATER WITH BLOWER SYSTEM given for printing Ink quick drying at bag output side of machine.